

FLOS

FA53000756.A Matte Stainless Steel


A-Rise 130

Designed by FLOS Outdoor, 2012



4W - 199lm - 4000K - CRI> 80 - Beam° 120

Mains voltage LED light source included. Requires a junction box to be ordered separately. The luminaire is equipped with a protruding, neoprene, 250 mm cable with an integrated 2-way, 3-pole H2O STOP connection system guaranteeing the water tightness of the connection. Frosted glass.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8054793649788
Mounting	In-ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	4
System power (W)	4
Source flux (lm)	400
Lumen Output (lm)	199

Physical

Colour	Matte Stainless Steel
Orientation	Fixed
Net weight (kg)	0.53
Package height (mm)	175
Package width (mm)	135
Package length (mm)	135
IP internal	67
IP external	66

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP



Technical Drawings

[2D](#)  ZIP


[3D](#)  ZIP



Ecodesign and Energy Labelling

  Non-replaceable light source

Schematic light drawing



Beam Angle: 120°

h(m)	E(lx)	D(m)
1	54	3.49
2	13	6.98
3	6	10.48
4	3	13.97
5	2	17.46

Luminous flux luminaire
199 lm

Photometric

Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	120
Beam angle C90-270 (°)	120
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-230
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Accessories & Power Supply



REQUIRED Accessory

FA50

Box for Installation A-Rise 130



OPTIONAL Accessory

F990C010000

3/4 way terminal block 4 poles
IP68 H2O stop. (ø5,5÷12mm
cable)



OPTIONAL Accessory

F990E00A000

S.P.D. (SURGE PROTECTION
DEVICE)