

# FLOS

FA53000956 Matte Stainless Steel


## A-Rise 130 Low Voltage

Designed by FLOS Outdoor, 2012

4W - 200lm - 4000K - CRI> 80 - Beam° 120



LED light source included. 24V remote electric power supply to be ordered separately, ON/OFF and adjustable light intensity from 1 to 10V or DALI. Requires a junction box to be ordered separately. The luminaire is equipped with a protruding, neoprene, 250 mm cable with an integrated H2O STOP connection system and a wiring kit with crimp connectors and adhesive heat-shrink tubing guaranteeing the water tightness of the connection. Frosted glass.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8054793649832
Mounting	In-ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	4
System power (W)	4
Source flux (lm)	380
Lumen Output (lm)	200

### Physical

Colour	Matte Stainless Steel
Orientation	Fixed
Net weight (kg)	0.46
Package height (mm)	95
Package width (mm)	140
Package length (mm)	140
IP internal	67
IP external	66

### Download

[Mounting instructions](#)  ZIP

### Photometric Files

[LDT / IES](#)  ZIP

### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP


### Ecodesign and Energy Labelling



Non-replaceable light source



## Schematic light drawing



Beam Angle: 120°

h(m)	E(lx)	D(m)
1	54	3.49
2	14	6.98
3	6	10.48
4	3	13.97
5	2	17.46

Luminous flux luminaire  
200 lm

## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	120
Beam angle C90-270 (°)	120
Extreme cut off	No

## Electrical

Insulation class	III
Power supply	Remote excluded
Power supply type	Dimmable
Emergency	No

## Accessories & Power Supply



REQUIRED  
Accessory

FA50

Box for Installation A-Rise 130



OPTIONAL  
Accessory

F990C050000

2 way terminal block 2 poles IP68  
H2O stop. ( $\varnothing 4 \pm 6,9$ mm cable)



OPTIONAL  
Power supply

RF25757

Power supply 24V 10W / 110-  
240V IP67 Class II selv.\_Non  
Dimmable



OPTIONAL  
Power supply

RF25752

Power supply 24Vdc 20W / 220-  
240V IP67 Class II selv. Non  
Dimmable



OPTIONAL  
Power supply

RF25747

Power supply 24V 10W / 110-240V  
IP20 Class II selv. Non Dimmable



OPTIONAL  
Power supply

RF25750

Power supply 24Vdc 17W / 110-  
240V (15W@110V) IP20 Class II  
selv. Dimmable Push-Dimm Or  
1.10V



OPTIONAL  
Power supply

F990B21A000

Power supply 17W/110+240V  
-24Vdc (15W@110V) IP67 Class II  
Selv. Dimmable Push-Dimm Or  
1.10V



OPTIONAL  
Power supply

F990B27A000

Power supply 24Vdc 70W / 220-  
240V IP67 Class I selv. Non  
Dimmable



OPTIONAL  
Power supply

F990B28A000

Power supply 24Vdc 50W / 220-  
240V IP67 Class I selv. Non  
Dimmable