

Almendra Linear Suspension 3 Primer


Designed by Patricia Urquiola, 2022

45W - 1338lm - 2700K - CRI> 95

Suspension lamp with diffused light emission available in linear and organic compositions. Tubular structure made of aluminium and CNC aluminium terminals with matte or metallized finish. Edge Lighting technology integrated. Light units can be turned by steps of 60° within the structure in order to change the direction of the light emitted. Metal rosette with primer finish. The integrated electronics in the ceiling rose allow the use of different dimming systems: 1-10V, DALI, push-dim or potentiometer. Useful length of the cable 3 mt. The product has been designed according to the ISCC standards and it is assembled with total absence of glued components so that it can be completely separated for future recyclability.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607050729
Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Edge Lighting
Power (W)	45
Lumen Output (lm)	1338

Physical

Colour	Bay Blue Metallized
Length (mm)	1286
Cord colour	Clear
Canopy colour	Primer
Canopy length/diameter (mm)	420
Canopy width (mm)	70
Canopy height (mm)	39
Net weight (kg)	7.14
Package volume (m3)	0.15
IP internal	20

Download

Mounting instructions [Download PDF](#)

Photometric Files


LDT / IES [Download LDT](#)

Technical Drawings


2D [Download ZIP](#)

3D [Download ZIP](#)

[Bim](#) [Download ZIP](#)



Schematic light drawing



Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	95

Electrical


Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 0-10V, Dimmable 1-10V, Dimmable DALI 1, Dimmable Push
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Spare Parts



- | | | |
|-----|---|-----------|
| 01. | Driver 96W 48V 220-240V | RF32405 |
| 02. | Led dimmer kit | RF34197 |
| 04. | Terminal Joint L90 Almendra Bay Blue Metallized | RF32777 |
| 05. | Assembly Almendra Suspension Wiring & Connections Bay Blue Metallized | RF32534 |
| 06. | Assembly Almendra Suspension Central Feed Bay Blue Metallized | RF32525 |
| 08. | Almendra Suspension Bay blue body assembly | RF32518 |
| 09. | Kit with screws and allen key | RF3160100 |



RF32405

Driver 96W 48V 220-240V



RF34197

Led dimmer kit



RF32777

Terminal Joint L90 Almendra Bay
Blue Metallized

FLOS

RF32534

Assembly Almendra Suspension
Wiring & Connections Bay Blue
Metallized

FLOS

RF32525

Assembly Almendra Suspension
Central Feed Bay Blue Metallized

FLOS

RF32518

Almendra Suspension Bay blue
body assembly



RF3160100

Kit with screws and allen key