


# FLOS

F0396039 Bay Blue Metallized

## Almendra Organic Suspension Short 2 Primer

Designed by Patricia Urquiola, 2022




31W - 892lm - 2700K - CRI> 95

Suspension lamp with diffused light emission available in linear and organic compositions. Tubular structure made of aluminium and CNC aluminium terminals with matte or metallized finish. Edge Lighting technology integrated. Light units can be turned by steps of 60° within the structure in order to change the direction of the light emitted. Metal rosette with primer finish. The integrated electronics in the ceiling rose allow the use of different dimming systems: 1-10V, DALI, push-dim or potentiometer. Useful length of the cable 3 mt. The product has been designed according to the ISCC standards and it is assembled with total absence of glued components so that it can be completely separated for future recyclability.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

EAN	8059607051023
Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Edge Lighting
Power (W)	31
Lumen Output (lm)	892

### Physical

Colour	Bay Blue Metallized
Length (mm)	1326
Cord colour	Clear
Canopy colour	Primer
Canopy length/diameter (mm)	799
Canopy width (mm)	70
Canopy height (mm)	39
Net weight (kg)	8.17
Package volume (m3)	0.21
IP internal	20

### Download

Mounting instructions



### Photometric Files

LDT / IES



### Technical Drawings

2D



3D




BIM






## Schematic light drawing



## Ecodesesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional


## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	95

## Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 0-10V, Dimmable 1-10V, Dimmable DALI 1, Dimmable Push
Dimming interface	Remote Dimmable (Dimmer Not Included)

## Spare Parts



- |     |  |           |
|-----|--|-----------|
| 01. | Driver 96W 48V 220-240V                        | RF32405   |
| 02. | Led dimmer kit                                 | RF34197   |
| 03. | Almendra S Y primer cover                      | RF0429100 |
| 04. | Kit with screws and allen key                  | RF3160100 |
| 05. | Almendra Suspension Bay blue body assembly     | RF32518   |
| 06. | Almendra S Arc/Y terminal joint L31 Met. Green | RF33250   |



RF32405

Driver 96W 48V 220-240V



RF34197

Led dimmer kit




RF0429100

Almendra S Y primer cover



RF3160100

Kit with screws and allen key



RF32518

Almendra Suspension Bay blue body assembly



RF33250

Almendra S Arc/Y terminal joint L31 Met. Green