

FLOS


09.3850.18 Deep Brown

Atom 200

Designed by Piero Lissoni, 2018

10.5W - 424lm - 3000K - CRI> 90 - Beam° 110

General lighting LED module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module non-dimmable. To individually control the lights, select integrated Casambi versions. Not suitable for vertical installations.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	10.5
Source flux (lm)	1079
Lumen Output (lm)	424
Efficacy (lm/W)	41

Physical

Colour	Deep Brown
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	192
Net weight (kg)	0.47
IP internal	20

Download

[Mounting instructions](#) PDF

[Item information](#) JPG

Photometric Files

[LDT / IES](#) ZIP

Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	110
Beam angle C90-270 (°)	110
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	420
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable

Ecodesign and Energy

Labelling

