

FLOS

FA10017440 Opal

C-Me Round 70 Rgb


Designed by FLOS Outdoor, 2008



LED source included. Remote electric power supply with DMX 3chx350mA interface, to be ordered separately. Requires a junction box to be ordered separately. The luminaire is equipped with a protruding, neoprene, 200 mm cable and a wiring kit with crimp connectors and adhesive heat-shrink tubing guaranteeing the water tightness of the connection. Extra clear transparent glass.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|----------------------|
| EAN | 8054793604978 |
| Mounting | In-ground |
| Environments | Outdoor wet location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Number of lamps | 1 |
| Power (W) | 3 |
| System power (W) | 3.4 |

Physical

| | |
|---------------------|-------|
| Colour | Opal |
| Orientation | Fixed |
| Net weight (kg) | 0.37 |
| Package height (mm) | 90 |
| Package width (mm) | 140 |
| Package length (mm) | 140 |
| IP internal | 67 |
| IP external | 66 |

Download

[Mounting instructions](#)  ZIP

Ecodesign and Energy Labelling

   Replaceable (LED only) light source by a professional



Photometric

| | |
|--------------------|-----------|
| Light distribution | Symmetric |
| CCT (K) | RGB |
| Extreme cut off | No |

Electrical

| | |
|--------------------|---|
| Insulation class | III |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 24 |
| Power supply | Remote excluded |
| Dimmable | Yes |
| Power supply type | Dimmable DMX |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |
| Emergency | No |

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance'

Dimmable version on request

Accessories & Power Supply



REQUIRED Power supply

F990B22A000

Power supply with DMX interface for RGB fixtures 36W/220÷240v-3CH x 350mA (3CH x 10 x 1W)
DMX control allowed IP67 Class I Selv Eq.



REQUIRED Accessory

FA101

Box for Installation C-Me Round 70/90



OPTIONAL Accessory

F990B10A000

DMX controller; dimmer switch for recessed box (60mm hole centres)



OPTIONAL Accessory

F990B11A000

DMX controller; stand-alone/pc interface.



OPTIONAL Accessory

F990B13A000

DMX splitter 512



OPTIONAL Accessory

F990B12A000

DMX cable - shielded twisted pair with 110 Ohm constant impedance