

# FLOS



F011A32F030.A Black/Black Lava

## Captain Flint Outdoor H 1537 mm Black/Black Lava

Designed by Michael Anastassiades, 2017



694lm - 3000K - CRI> 80 - Beam° 110

LED bulb included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100%. Casambi function on demand.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                      |
|------------------------|----------------------|
| EAN                    | 8054793211015        |
| Mounting               | Floor                |
| Environments           | Outdoor wet location |
| Light source type      | LED                  |
| Light sources included | Yes                  |
| LED type               | LED array            |
| System power (W)       | 11                   |
| Source flux (lm)       | 1140                 |
| Lumen Output (lm)      | 694                  |

### Physical

|                         |                  |
|-------------------------|------------------|
| Colour                  | Black/Black Lava |
| Trim                    | No               |
| Orientation             | Adjustable       |
| Transversal tilting (°) | 270              |
| Net weight (kg)         | 14.35            |
| IP internal             | 65               |

### Download

Mounting instructions [Download ZIP](#)

### Photometric Files

LDT / IES [Download ZIP](#)

### Technical Drawings


2D [Download ZIP](#)

3D [Download ZIP](#)

[Bim](#) [Download ZIP](#)



Schematic light drawing



Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 3000      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 110       |
| Beam angle C90-270 (°) | 110       |
| Extreme cut off        | No        |

Electrical

|                    |                                     |
|--------------------|-------------------------------------|
| Insulation class   | II                                  |
| Frequency (Hz)     | 50/60                               |
| Main voltage (Vac) | 100-240                             |
| Power supply       | Remote included                     |
| Dimmable           | Yes                                 |
| Power supply type  | Dimmer on board                     |
| Dimming interface  | Switch Integrated (Remote Dimmable) |
| Emergency          | No                                  |