

FLOS

F1840044 Anodized Champagne


Coordinates Ceiling 4 CLIII

Designed by Michael Anastassiades, 2020

147W - 8830lm - 2700K - CRI> 95



Coordinates is a lighting system with diffuse light composed of horizontal and vertical luminaires arranged in a bright grid of various shapes and complexities. Each element is made of extruded anodized aluminium with a champagne finish and a diffuser in platinum optical silicone with an integrated LED strip (CRI 95). Each element is powered and supported by an invisible electrical and mechanical connection designed specifically to allow for the composition of the 1 ceiling models C4, its geometry was designed to be repeated to create large grids for custom installations. Each Coordinates configuration must include its own ceiling rose, whose integrated electronics allow for the use of different dimmer systems: push, 1-10, DALI. In the absence of these systems, the amount of light can be set during installation with the push system included in the rose. The related CL III version is also available for each configuration for installations with a remote power supply.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)


Main specifications

EAN	8059607033203
Mounting	Ceiling
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	147
Lumen Output (lm)	8830

Physical

Colour	Anodized Champagne
Length (mm)	1770
Net weight (kg)	5.2
Package volume (m3)	0.05
IP internal	20

Download

[Mounting instructions](#)  PDF

Photometric Files

[ULD](#)  ZIP

Technical Drawings

[3D](#)  ZIP

[Bim](#)  ZIP



Photometric

Lighting type	Total
Light distribution	Asymmetric
CCT (K)	2700
CRI>	95
Extreme cut off	No

Electrical

Insulation class	III
Main voltage (Vac)	48
Power supply	Remote excluded
Power supply type	Electronic 48V
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Accessories & Power Supply



OPTIONAL

RF29209

48Vdc 180W Power supply




OPTIONAL

RF26994

12-48V Led Dimmer

Spare Parts



- | | | |
|-----|---|---------|
| 01. | Rod Assembly L920 C-09
Anodized Champagne | RF30993 |
| 02. | Coordinates Ceiling 4 Rod
Assembly L920 C-08 Anodized
Champagne | RF30992 |
| 03. | Coordinates Rod Assembly L1760
H-10 Anodized Champagne | RF30984 |
| 04. | Coordinates Rod Assembly L1760
H-11 Anodized Champagne | RF30985 |
| 05. | Coordinates C4 Cl. III Rod
Assembly L920 CA-45 Anodized
Champagne | RF31463 |



RF30993
Rod Assembly L920 C-09
Anodized Champagne



RF30992
Coordinates Ceiling 4 Rod
Assembly L920 C-08 Anodized
Champagne



RF30984
Coordinates Rod Assembly L1760
H-10 Anodized Champagne



RF30985
Coordinates Rod Assembly L1760
H-11 Anodized Champagne



RF31463
Coordinates C4 Cl. III Rod
Assembly L920 CA-45 Anodized
Champagne