

FLOS

05.9210.40.78 White/White


Light Shadow Spot 45 Non Dimmable

Designed by FLOS Architectural, 2022

11.5W - 744lm - 4000K - CRI> 90 - Beam° 15



Projector to be installed on threephase track with LED light source. Built-in 220-240V, 50-60Hz power supply. All finishes come with black track adapter, arm and back of the head. In the "all white" versions the track adapter, arm and back of the head come in white. The display is always offered in high loss technical black anti-glare finish. For other finishes, please consult us.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

| | |
|------------------------|---------------------|
| Mounting | Track |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | LED array |
| Number of lamps | 1 |
| Power (W) | 11.5 |
| Source flux (lm) | 915 |
| Lumen Output (lm) | 744 |

Physical

| | |
|--------------------------|-------------|
| Colour | White/White |
| Orientation | Adjustable |
| Rotation (°) | 360 |
| Longitudinal tilting (°) | 90 |
| Net weight (kg) | 0.3 |
| IP internal | 20 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Beam Angle: 15°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 9171 | 0.27 |
| 2 | 2293 | 0.54 |
| 3 | 1019 | 0.80 |
| 4 | 573 | 1.07 |
| 5 | 367 | 1.34 |

9171 cd

Photometric

| | |
|--------------------------|-----------------------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 4000 |
| CRI> | 90 |
| Rf fidelity index | 92 |
| Rg gamut index | 99 |
| LED Life / Failure Ratio | L80B50>47.000h_Tc85°C |
| Beam angle C0-180 (°) | 15 |
| Beam angle C90-270 (°) | 15 |
| UGR _L | <10 |

Electrical

| | |
|--------------------|--------------|
| Insulation class | II |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| LED current (mA) | 250 |
| Power supply | Integrated |
| Dimmable | No |
| Power supply type | Non Dimmable |
| Dimming range (%) | N/A |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Accessories & Power Supply



OPTIONAL
Filter

08.0793.00

Honeycomb



OPTIONAL
Filter

Optical

08.0794.00

CCT Inceaser Filter D58



OPTIONAL
Filter

Optical

08.0795.00

CCT Decreaser Filter