

# FLOS

05.9244.14 Black

## Light Shadow Spot 60 Non Dimmable

Designed by FLOS Architectural, 2022

22W - 1445lm - 4000K - CRI> 90 - Beam° 43



Projector to be installed on threephase track with LED light source. Built-in 220-240V, 50-60Hz power supply. All finishes come with black track adapter, arm and back of the head. In the "all white" versions the track adapter, arm and back of the head come in white. The display is always offered in high loss technical black anti-glare finish. For other finishes, please consult us.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	22
Source flux (lm)	1815
Lumen Output (lm)	1445

### Physical

Colour	Black
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Net weight (kg)	0.5
IP internal	20

### Download

[Mounting instructions](#) PDF

### Photometric Files

[LDT / IES](#) ZIP


### Technical Drawings

[2D](#) ZIP

[3D](#) ZIP



## Schematic light drawing



Beam Angle: 43°

h(m)	E(lx)	D(m)
1	3146	0.79
2	787	1.59
3	350	2.38
4	197	3.17
5	126	3.97

Luminous flux luminaire  
1445 lm

## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	90
Rf fidelity index	92
Rg gamut index	99
LED Life / Failure Ratio	L80B50>47.000h_Tc85°C
Beam angle C0-180 (°)	43
Beam angle C90-270 (°)	43
UGR <sub>L</sub>	<16

## Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
LED current (mA)	500
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming range (%)	N/A

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



## Accessories & Power Supply



OPTIONAL  
Accessory

08.0175.14

Honeycomb



OPTIONAL  
Accessory

08.0176.14

Honeycomb



OPTIONAL  
Filter

Optical

08.0796.00

CCT Inceaser Filter D58



OPTIONAL  
Filter

Optical

08.0797.00

CCT Decreaser Filter D12



OPTIONAL  
Filter

Optical

08.0798.00

CCT Inceaser Filter D58



OPTIONAL  
Filter

Optical

08.0799.00

CCT Decreaser Filter D12