

# FLOS

06.2606.40 White

## Live End Feed Dimmable

Designed by FLOS Architectural, 2023




Wall surface, Ceiling surface

Feed unit for remote power supply unit. Power cable inserting is possible both from the Rear and the side.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting Wall surface, Ceiling surface

Environments Indoor dry location

Light sources included No

### Physical

Colour White

Net weight (kg) 0.02

IP internal 20

### Download

[Mounting instructions](#)



### Electrical

Insulation class III

Forward voltage (V) 24


Power supply Remote excluded

Dimmable Yes

Power supply type Dimmable

Dimming interface Remote Dimmable (Dimmer Not Included)

## Accessories & Power Supply



REQUIRED  
Power supply

Electrical

60.9352

LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.

REQUIRED  
Power supply

Electrical

60.9777A

Remote Power Supply Non Dimmable 24V. 120W. 220/240V

REQUIRED  
Power supply

Electrical

60.9705A

Remote Power Supply Non Dimmable 24V. 60W. 220/240V

OPTIONAL  
Power supply

Electrical

08.0613.14A

Dimmable control box 1-10V, 24/48V. For remote installation.