

FLOS


FA52516430 Black

Perseo 4 Asymmetric Optic

Designed by FLOS Outdoor, 2012



LED source included. Integrated power supply 220-240V ON-OFF and dimmable 1-10V or DALI. Graduated fixing bracket included. Equipped with a M20x1.5 cable guide (for 7mm<ø<13mm cables) and IP68 connector. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use. Optional accessories: protruding arm for walls; feet and arms to install the luminaire on a mast; wall-washer visor and anti-vandalism protection lid. Extraclear transparent glass.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8054793648354
Mounting	Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	53
Source flux (lm)	5859
Lumen Output (lm)	3085

Physical

Colour	Black
Orientation	Adjustable
Longitudinal tilting (°)	156
Net weight (kg)	5.06
Package height (mm)	155
Package width (mm)	265
Package length (mm)	430
Package volume (m3)	0.02
IP internal	65

Download

Mounting instructions  ZIP

Photometric Files

LDT / IES  ZIP


Technical Drawings

2D  ZIP

3D  ZIP



Schematic light drawing



Photometric

Light distribution	Asymmetric
CCT (K)	2700
CRI>	80
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional


Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL
Accessory
FA16730
Wall Washer Visor Perseo 4



OPTIONAL
Accessory
F990E00A000
S.P.D. (SURGE PROTECTION
DEVICE)



OPTIONAL
Pole
FA24806
Pole Ø76 mm h 3500 mm(with
Base)



OPTIONAL
Bracket
FA9606
Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm Double



OPTIONAL
Pole
FA415506
Pole Ø 102 mm h 5000 mm (+500
mm In-ground)



OPTIONAL
Pole
FA24833
Pole Ø76 mm h 3500 mm(with
Base)



OPTIONAL
Bracket
FA9006
Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Double



OPTIONAL
Bracket
FA9433
Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm



OPTIONAL
Bracket

FA11306

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Single



OPTIONAL
Bracket

FA11433

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Double



OPTIONAL
Bracket

FA7833

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Single



OPTIONAL
Bracket

FA9333

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 180 mm



OPTIONAL
Bracket

FA9033

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Double



OPTIONAL
Bracket

FA7906

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 500 mm Single



OPTIONAL
Bracket

FA9533

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 180 mm Double



OPTIONAL
Bracket

FA11406

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Double



OPTIONAL Bracket

FA7933

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 500 mm Single



OPTIONAL Bracket

FA8933

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 500 mm Double



OPTIONAL Pole

FA414533

Pole Ø 102 mm h 4000 mm (+500
mm In-ground)



OPTIONAL Pole

FA25006

Pole Ø76 mm h 3500 mm (+500
mm In-ground)



OPTIONAL Pole

FA25033

Pole Ø76 mm h 3500 mm (+500
mm In-ground)



OPTIONAL Pole

FA24906

Pole Ø76 mm h 4500 mm(with
Base)



OPTIONAL Pole

FA414506

Pole Ø 102 mm h 4000 mm (+500
mm In-ground)



OPTIONAL Pole

FA24933

Pole Ø76 mm h 4500 mm(with
Base)



OPTIONAL
Bracket

FA9406

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm



OPTIONAL
Pole

FA415033

Pole Ø 102 mm h 5000 mm With
Base



OPTIONAL
Bracket

FA9306

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 180 mm



OPTIONAL
Bracket

FA8906

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 500 mm Double



OPTIONAL
Bracket

FA11206

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Single



OPTIONAL
Accessory

FA116

Base Plate and Fixing Bolts for
Pole Ø 102 mm h 4000/5000 mm
with Base



OPTIONAL
Pole

FA25106

Pole Ø76 mm h 4500 mm (+500
mm In-ground)



OPTIONAL
Pole

FA25133

Pole Ø76 mm h 4500 mm (+500
mm In-ground)



OPTIONAL
Accessory

FA18130

Wall Bracket Perseo 4 1000 mm



OPTIONAL
Bracket

FA9633

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm Double



OPTIONAL
Pole

FA414006

Pole Ø 102 mm h 4000 mm With
Base



OPTIONAL
Pole

FA415006

Pole Ø 102 mm h 5000 mm With
Base



OPTIONAL
Bracket

FA9506

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 180 mm Double



OPTIONAL
Bracket

FA11233

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Single



OPTIONAL
Accessory

FA16830

Antivandal Louvre Perseo 4



OPTIONAL
Pole

FA414033

Pole Ø 102 mm h 4000 mm With
Base



OPTIONAL
Bracket

FA11533

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Double



OPTIONAL
Bracket

FA11506

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Double



OPTIONAL
Bracket

FA11333

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Single



OPTIONAL
Bracket

FA7806

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Single