


## SuperWire S3

Designed by Formafantasma, 2025

90W - 6450lm - 2700K - CRI> 90

SuperWire is the first family of modular lamps designed by Formafantasma for Flos. A magical and poetic project, with an essential design but a great stage presence, which recalls the work of the great glass masters of the last century. Made of planar glass and polished aluminum, its design originated from the development of a custom-made light source that emits a warm and homogeneous light. Made up of one or more hexagons of planar glass connected by a polished aluminum element, SuperWire lights up its entire surface thanks to a new source: a very thin, flat, soft, flexible LED strip measuring up to one meter, which emits a warm and homogeneous light along its entire length and which can be easily removed for replacement and repair, unique in the panorama of LED bulb-less lamps. Suspension models feature a concealed downlight module for functional accent lighting on tables, complemented by the warm, diffuse glow of the vertical modules.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| EAN                    | 8059607073698       |
| Mounting               | Suspension          |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Filament LED        |
| Power (W)              | 90                  |
| Lumen Output (lm)      | 6450                |

### Physical

|                             |       |
|-----------------------------|-------|
| Colour                      | Steel |
| Length (mm)                 | 295   |
| Canopy length/diameter (mm) | 216   |
| Canopy width (mm)           | 216   |
| Canopy height (mm)          | 47    |
| Net weight (kg)             | 22    |
| Package volume (m3)         | 0.33  |
| IP internal                 | 20    |

### Download

Mounting instructions



PDF

### Photometric Files

ULD



ULD

### Technical Drawings

2D



ZIP

3D



ZIP



Photometric


|                    |            |
|--------------------|------------|
| Lighting type      | Total      |
| Light distribution | Asymmetric |
| CCT (K)            | 2700       |
| CRI>               | 90         |
| Extreme cut off    | No         |

Electrical


|                    |                   |
|--------------------|-------------------|
| Insulation class   | I                 |
| Frequency (Hz)     | 50/60             |
| Main voltage (Vac) | 100-240           |
| Power supply       | Remote included   |
| Dimmable           | Yes               |
| Power supply type  | Dimmable          |
| Dimming interface  | Dimmer Integrated |
| Batteries inside   | No                |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by an end-user



Replaceable control gear by an end-user



00.      Led dimmer kit      RF34197



RF34197

Led dimmer kit