

# FLOS

05.4571.40.DA White

## The Glowing Track 360 Surface Remote Driver Dali

Designed by FLOS Architectural, 2025




Length: 1210 - Surface

360° surface ambient lighting system that provides uniform light distribution. Available in four lengths (600 mm, 1200 mm, 1800 mm, and 2400 mm). Driver not included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Surface             |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 24.8                |
| System power (W)       | 27.6                |
| Source flux (lm)       | 2968                |
| Lumen Output (lm)      | 2130                |

### Physical

|             |       |
|-------------|-------|
| Colour      | White |
| Orientation | Fixed |
| Length (mm) | 1210  |
| IP internal | 20    |

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)



### Ecodesign and Energy Labelling



## Schematic light drawing



### Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Total                 |
| Light distribution       | Symmetric             |
| CCT (K)                  | 3000                  |
| CRI>                     | 90                    |
| McAdam steps (SDCM)      | 3                     |
| Rf fidelity index        | 92                    |
| Rg gamut index           | 89                    |
| LED Life / Failure Ratio | L80B10>72.000h_Tc65°C |

### Electrical

|                   |                                       |
|-------------------|---------------------------------------|
| Insulation class  | III                                   |
| Power supply      | Remote                                |
| Dimmable          | Yes                                   |
| Power supply type | Dimmable DALI 2                       |
| Dimming range (%) | 1-100                                 |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |
| Batteries inside  | No                                    |

## Accessories & Power Supply




REQUIRED  
Power supply

Electrical

60.9777A

Remote Power Supply Non  
Dimmable 24V. 120W. 220/240V



REQUIRED  
Accessory

Installation

08.0615.40

Ceiling fixing kit



OPTIONAL  
Connector

08.1205.40

Linear Joint Surface



OPTIONAL  
Connector

08.1206.40

Corner Joint 2  
Suspension/Surface



OPTIONAL  
Connector

08.1207.40

Corner Joint 3  
Suspension/Surface



OPTIONAL  
Connector

08.1208.40

Corner Joint 4  
Suspension/Surface