

UT Pro Surface 150 On Board Dimmer Included

Designed by FLOS Architectural, 2018



LED light source projector for surface installation. 120-277V power supply unit and potentiometer included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
System power (W)	20
Source flux (lm)	2294
Lumen Output (lm)	1701

Physical

Colour	White
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Net weight (kg)	0.52
IP internal	20



Download

Mounting instructions [Download PDF](#)

Photometric Files

LDT / IES [Download ZIP](#)


Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	80
LED Life / Failure Ratio	L80B50 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	35
Beam angle C90-270 (°)	35
Extreme cut off	No
UGR _L	<10

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	120-277
LED current (mA)	500
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmer on board
Dimming range (%)	10-100
Dimming interface	Dimmer Integrated

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

Accessories & Power Supply



OPTIONAL
Accessory
Optical

08.0526.00


Snoot shielding cone



OPTIONAL
Accessory
Optical

08.8428.00

Honeycomb



OPTIONAL
Accessory
Optical

08.8429.00

Screening crosspiece



OPTIONAL
Accessory
Optical

08.8431.00

Elliptical lens



OPTIONAL
Accessory
Optical

08.8432.00


Flood lens



OPTIONAL
Accessory
Optical

08.0526.40

Snoot shielding cone



OPTIONAL
Accessory
Optical

08.0526.BW

Snoot shielding cone