


90° Corner Feed Non Dimmable

NEW

Designed by FLOS Architectural, 2023




Ceiling surface, Wall surface

90° flat corner. Can be powered. It has a rear space for the supply connection. Rear feeding cable entry.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                               |
|------------------------|-------------------------------|
| Mounting               | Ceiling surface, Wall surface |
| Environments           | Indoor dry location           |
| Light sources included | No                            |

### Physical

|                 |               |
|-----------------|---------------|
| Colour          | Brushed Steel |
| Net weight (kg) | 0.02          |
| IP internal     | 20            |

### Download

Mounting instructions



### Photometric

|                 |    |
|-----------------|----|
| Extreme cut off | No |
|-----------------|----|

### Electrical


|                     |                 |
|---------------------|-----------------|
| Insulation class    | III             |
| Forward voltage (V) | 24              |
| Power supply        | Remote excluded |
| Dimmable            | No              |
| Power supply type   | Non Dimmable    |

Accessories & Power Supply



REQUIRED  
Power supply  
Electrical

60.9352  
LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.




REQUIRED  
Power supply  
Electrical

60.9705  
Remote Power Supply Non Dimmable 24V. 60W. 220/240V




REQUIRED  
Power supply  
Electrical

60.9777A  
Remote Power Supply Non Dimmable 24V. 120W. 220/240V




OPTIONAL  
Power supply  
Electrical

08.0613.14A  
Dimmable control box 1-10V, 24/48V. For remote installation.



OPTIONAL  
Component  
Installation

06.2618.40A  
Track Cover 3000mm



OPTIONAL  
Component  
Installation

06.2618.14A  
Track Cover 3000mm



OPTIONAL  
Connector  
Electrical

06.2608.14  
Straight Connector



OPTIONAL  
Connector  
Electrical

06.2608.40  
Straight Connector