

# FLOS

06.1648.14 Black

## 90° Corner. Can be powered


Designed by FLOS Architectural, 2015



Length: 150 - Wall recessed, Ceiling recessed

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Wall recessed, Ceiling recessed
Environments	Indoor dry location
Light sources included	no

### Physical

Colour	Black
Trim	No
Recessed depth (mm)	86
Length (mm)	150
Net weight (kg)	0.76
IP internal	20
IP external	20

### Download

[Mounting instructions](#)



### Photometric

Extreme cut off No

### Electrical

Forward voltage (V) 24

## Accessories & Power Supply



OPTIONAL  
Power supply

Electrical

60.9352

LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.



OPTIONAL  
Power supply

Electrical

60.9089

Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W



OPTIONAL  
Power supply

Electrical

60.9407

Electronic transformer with constant voltage (24V) for LED. 100/240V. 120W



OPTIONAL  
Installation

08.8865.14A

Endcap. 2 unit kit