

# FLOS

FA51309206 Grey

## Aimer 2 Pole 900

NEW


Designed by FLOS Outdoor, 2011



LED source included. Remote electrical power supply 24V dc ON/OFF to be ordered separately. Equipped with a 2000 mm protruding section of neoprene cable and a 2-pole and 3-way connection box with H2O STOP system that guarantee the tightness of the connection. Extraclear transparent glass. Metal nail for ground installation included. Dimmable version available upon request.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

EAN	8054793633459
Mounting	Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	2
System power (W)	3.4
Source flux (lm)	199
Lumen Output (lm)	138

### Physical

Colour	Grey
Orientation	Directional
Longitudinal tilting (°)	174
Net weight (kg)	1.28
Package height (mm)	120
Package width (mm)	1450
Package length (mm)	117
Package volume (m3)	0.02
IP internal	65

### Download

Mounting instructions [ZIP](#)



### Photometric Files

LDT / IES



### Technical Drawings

2D



3D




### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



## Schematic light drawing



Beam Angle: 13°		
h(m)	E(k)	D(m)
1	3025	0.22
2	756	0.44
3	336	0.67
4	189	0.89
5	121	1.11

## Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	12
Beam angle C90-270 (°)	12
Extreme cut off	No

## Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	24
Power supply	Remote excluded
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

## Notes

Dimmable version on request

## Accessories & Power Supply



### OPTIONAL Power supply

RF2572

Power supply 24Vdc 20W / 220-240V IP67 Class II selv. Non Dimmable



### OPTIONAL Power supply

RF25757

Power supply 24V 10W / 110-240V IP67 Class II selv.\_Non Dimmable



### OPTIONAL Accessory

F990C010000

3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)



### OPTIONAL Power supply

F990B27A000

Power supply 24Vdc 70W / 220-240V IP67 Class I selv. Non Dimmable



### OPTIONAL Accessory

FA136

Ground Spike Aimer 1/Aimer 2/Aimer 3/Perseo 2



### OPTIONAL Power supply

FA235

Power supply 8W/110÷240V - 24Vdc IP67 Class II selv. Eq.



### OPTIONAL Power supply

RF25747

Power supply 24V 10W /110-240V IP20 Class II selv. Non Dimmable



### OPTIONAL

F990B34A000

Power Supply dual function C.V. Vout 24Vdc 8W, Vin 220÷240V C.C. Iout 350mA: 8W, Vin 220÷240V IP 20 Class II Selv. NON Dimmable



OPTIONAL  
Power supply

RF25748

Power Supply dual function C.V.  
Vout 24Vdc 8W, Vin 220÷240V  
C.C. Iout 350mA: 8W, Vin  
220÷240V IP 65 Class II Selv.  
NON Dimmable



OPTIONAL  
Power supply

F990B28A000

Power supply 24Vdc 50W / 220-  
240V IP67 Class I selv. Non  
Dimmable