

# FLOS


FA10017441 Transparent

## C-Me Square 70 Rgb NEW

Designed by FLOS Outdoor, 2008



LED source included. Remote electric power supply with DMX 3chx350mA interface, to be ordered separately. Requires a junction box to be ordered separately. The luminaire is equipped with a protruding, neoprene, 200 mm cable and a wiring kit with crimp connectors and adhesive heat-shrink tubing guaranteeing the water tightness of the connection. Extra clear transparent glass.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8054793604985
Mounting	In-ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	3
System power (W)	3.4

### Physical

Colour	Transparent
Orientation	Fixed
Net weight (kg)	0.41
Package height (mm)	134
Package width (mm)	134
Package length (mm)	83
IP internal	67
IP external	66

### Download

[Mounting instructions](#)  ZIP

### Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional

## Photometric

Light distribution	Symmetric
CCT (K)	RGB
Extreme cut off	No

## Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable DMX
Dimming interface	Remote Dimmable (Dimmer Not Included)
Emergency	No

## Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance'

Dimmable version on request

---

## Accessories & Power Supply



**REQUIRED**  
Power supply

F990B22A000

Power supply with DMX interface for RGB fixtures 36W/220÷240v-3CH x 350mA (3CH x 10 x 1W)  
DMX control allowed IP67 Class I Selv Eq.



**REQUIRED**  
Accessory

FA102

Box for Installation C-Me Square 70



**OPTIONAL**  
Accessory

F990B10A000

DMX controller; dimmer switch for recessed box (60mm hole centres)



**OPTIONAL**  
Accessory

F990B11A000

DMX controller; stand-alone/pc interface.



**OPTIONAL**  
Accessory

F990B13A000

DMX splitter 512



**OPTIONAL**  
Accessory

F990B12A000

DMX cable - shielded twisted pair with 110 Ohm constant impedance