

FLOS

SA.1051.1 Raw

Circle of Light Plate 600 mm


Designed by FLOS Architectural, 2013

Lighting system, seamless ceiling mounted, for 24 individual LED lighting spots. Set of 12 spots, complete with junction box, power supply and cables, has to be ordered separately. The 1-10V version is dimmable from 10% to 100%.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Number of lamps	24

Physical

Colour	Raw
Trim	No
Recessed depth (mm)	150
Length (mm)	950
Net weight (kg)	16.30
IP internal	20

Download

[Mounting instructions](#)  PDF

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Photometric

Lighting type	Direct
Light distribution	Symmetric
Extreme cut off	No

Notes

Accent Lighting and General Lighting: 2 units must be ordered (accessories).

Accessories & Power Supply



REQUIRED
Accessory

Electrical

08.8572.14D

Accent Lighting 3000K. Set of 12 spots for circle of light. Non Dimmable



REQUIRED
Accessory

Electrical

08.8572.14D1V

Accent Lighting 3000K. Set of 12 spots for circle of light. Dimmable 1-10V



REQUIRED
Accessory

Electrical

08.8572.14DDA

Accent Lighting 3000K. Set of 12 spots for circle of light. Dimmable DALI



REQUIRED
Accessory

Electrical

08.8573.14D

General Lighting 3000K. Set of 12 spots for circle of light. Non Dimmable



REQUIRED
Accessory

Electrical

08.8573.14D1V

General Lighting 3000K. Set of 12 spots for circle of light. Dimmable 1-10V



REQUIRED
Accessory

Electrical

08.8573.14DDA

General Lighting 3000K. Set of 12 spots for circle of light. Dimmable Dali



REQUIRED
Accessory

08.8662.14D

Accent Lighting. Set of 12 spots 2700K CRI 90



REQUIRED
Accessory

08.8662.14D1V

Accent Lighting. Set of 12 spots 2700K CRI 90. Dimmable 1-10C



REQUIRED
Accessory

08.8662.14DDA

Accent Lighting. Set of 12 spots
2700K CRI 90. Dimmable DALI



REQUIRED
Accessory

08.8663.14D

General Lighting. Set of 12 spots
2700K CRI 90



REQUIRED
Accessory

08.8663.14D1V

General Lighting. Set of 12 spots
2700K CRI 90. Dimmable 1-10V



REQUIRED
Accessory

08.8663.14DDA

General Lighting. Set of 12 spots
2700K CRI 90. Dimmable DALI