

Data Connection Rod Rose Ø 50 mm


Designed by Vincent Van Duysen, 2018



Data connection rod rose ø50mm. Use one for each line of the installation, for connection to DALI or 1-10V signal source. Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light sources included	no

Physical

Colour	White
Trim	No
Length (mm)	300
Net weight (kg)	0.55
IP internal	20
IP external	20

Download

Mounting instructions

↓ PDF

Electrical

Power supply	Remote excluded
Power supply type	Non Dimmable, Dimmable 1-10V, Dimmable DALI 1
Emergency	No

Notes

The closure terminals will also be electrified and must be ordered separately. Data connection rod rose ø50 mm: Use one for each line of the installation, for connection to DALI or 1-10V signal source. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED
Power supply
Electrical

60.8919
LED Power Supply Source for
remote installation. 48V/320W.
100/240 Vac



REQUIRED
Power supply
Electrical

60.9170
LED power supply source for
remote installation, 48V/120W.
220/240 Vac



REQUIRED
Power supply
Electrical

60.9607
LED power supply source for
remote installation, 110Vac-150W
/ 220Vac-200W



REQUIRED
Component
06.5135.14A
End Cap Dali/1-10V/FLOS
Control® by Casambi compatible




REQUIRED
Component
06.5135.40A
End Cap Dali/1-10V/FLOS
Control® by Casambi compatible



REQUIRED
Component
06.5142.14A
End Cap On board dimmer/FLOS
Control® by Casambi compatible



REQUIRED
Component
06.5142.40A
End Cap On board dimmer/FLOS
Control® by Casambi compatible



OPTIONAL
Power supply
Electrical
08.0613.14A
Dimmable control box 1-10V,
24/48V. For remote installation.