

## Data Connection Rod Rose Ø 50 mm

Designed by Vincent Van Duysen, 2018



Data connection rod rose ø50mm. Use one for each line of the installation, for connection to DALI or 1-10V signal source. Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light sources included | no                  |

### Physical

|                 |       |
|-----------------|-------|
| Colour          | Black |
| Trim            | No    |
| Length (mm)     | 700   |
| Net weight (kg) | 0.748 |
| IP internal     | 20    |
| IP external     | 20    |



### Download

Mounting instructions

↓ PDF

### Electrical

|                   |                                                     |
|-------------------|-----------------------------------------------------|
| Power supply      | Remote excluded                                     |
| Power supply type | Non Dimmable,<br>Dimmable 1-10V,<br>Dimmable DALI 1 |
| Emergency         | No                                                  |

## Notes

The closure terminals will also be electrified and must be ordered separately. Data connection rod rose  $\varnothing 50$  mm: Use one for each line of the installation, for connection to DALI or 1-10V signal source. Adjustable 25 mm, to adapt it to irregular ceilings.

---

Accessories & Power Supply



REQUIRED  
Power supply  
Electrical

60.8919  
LED Power Supply Source for  
remote installation. 48V/320W.  
100/240 Vac



REQUIRED  
Power supply  
Electrical

60.9170  
LED power supply source for  
remote installation, 48V/120W.  
220/240 Vac



REQUIRED  
Power supply  
Electrical

60.9607  
LED power supply source for  
remote installation, 110Vac-150W  
/ 220Vac-200W



REQUIRED  
Component  
06.5135.14A  
End Cap Dali/1-10V/FLOS  
Control@ by Casambi compatible




REQUIRED  
Component  
06.5135.40A  
End Cap Dali/1-10V/FLOS  
Control@ by Casambi compatible



REQUIRED  
Component  
06.5142.14A  
End Cap On board dimmer/FLOS  
Control@ by Casambi compatible



REQUIRED  
Component  
06.5142.40A  
End Cap On board dimmer/FLOS  
Control@ by Casambi compatible



OPTIONAL  
Power supply  
Electrical  
08.0613.14A  
Dimmable control box 1-10V,  
24/48V. For remote installation.