

# FLOS


FA54200906 Grey

**Eclipse** **NEW**

Designed by FLOS Outdoor, 2013



Slim LED source included. Remote electrical power supply 24V dc to be ordered separately. Equipped with a 300mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Dimmable. round luminaire for installation on wall – surface mounted. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content), stainless steel bracket and transparent polycarbonate emitting unit. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65 In compliance with EN60598-1 standards Class of insulation: II; 24V version: III Installation: the luminaire is equipped with a piece of neoprene cable (approx. 200mm) for an easy-to-make connection. Direct screwing on surface through the stainless steel bracket. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire. During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating. Damages on the coating exposed to outdoor conditions or water, could cause corrosion. Chemical substances affect the anticorrosion covering protection.



## Download

Mounting instructions



## Photometric Files

LDT / IES



## Technical Drawings

2D



3D



Are you a professional and your project needs consulting and support?

**BOOK AN APPOINTMENT**

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional

Main specifications


|                        |                      |
|------------------------|----------------------|
| EAN                    | 8054793694856        |
| Mounting               | Wall                 |
| Environments           | Outdoor wet location |
| Light source type      | LED                  |
| Light sources included | Yes                  |
| LED type               | Power LED            |
| Number of lamps        | 1                    |
| Power (W)              | 6                    |
| System power (W)       | 7.5                  |
| Source flux (lm)       | 739                  |
| Lumen Output (lm)      | 387                  |

Physical

|                     |       |
|---------------------|-------|
| Colour              | Grey  |
| Orientation         | Fixed |
| Net weight (kg)     | 0.95  |
| Package height (mm) | 40    |
| Package width (mm)  | 250   |
| Package length (mm) | 250   |
| IP internal         | 65    |



Schematic light drawing



Photometric

|                    |            |
|--------------------|------------|
| Light distribution | Asymmetric |
| CCT (K)            | 2700       |
| CRI>               | 80         |
| Extreme cut off    | No         |

Electrical

|                    |                                                                  |
|--------------------|------------------------------------------------------------------|
| Insulation class   | III                                                              |
| Frequency (Hz)     | 50/60                                                            |
| Main voltage (Vac) | 24                                                               |
| Power supply       | Remote excluded                                                  |
| Dimmable           | Yes                                                              |
| Power supply type  | Non Dimmable,<br>Dimmable, Dimmable<br>1-10V, Dimmable<br>DALI 1 |
| Dimming interface  | Remote Dimmable<br>(Dimmer Not<br>Included)                      |
| Emergency          | No                                                               |

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL  
Power supply

RF25752  
Power supply 24Vdc 20W / 220-240V IP67 Class II selv. Non Dimmable



OPTIONAL  
Power supply

RF25757  
Power supply 24V 10W / 110-240V IP67 Class II selv.,Non Dimmable



OPTIONAL  
Power supply

F990B27A000  
Power supply 24Vdc 70W / 220-240V IP67 Class I selv. Non Dimmable



OPTIONAL  
Power supply

RF25750  
Power supply 24Vdc 17W / 110-240V (15W@110V) IP20 Class II selv. Dimmable Push-Dimm Or 1.10V



OPTIONAL  
Power supply

F990B29A000  
Power supply 24Vdc 100W / 220-240V IP67 Class I selv.Non Dimmable



OPTIONAL  
Power supply

F990B21A000  
Power supply 17W/110÷240V -24Vdc (15W@110V) IP67 Class II Selv. Dimmable Push-Dimm Or 1.10V



OPTIONAL  
Power supply

RF25747  
Power supply 24V 10W /110-240V IP20 Class II selv. Non Dimmable



OPTIONAL  
Power supply

F990B28A000  
Power supply 24Vdc 50W / 220-240V IP67 Class I selv. Non Dimmable