

FLOS

06.5125.40 White

Electrical Feed Rod Rose Ø 140 mm


Designed by Vincent Van Duysen, 2017



Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light sources included	no
Number of lamps	1

Physical

Colour	White
Trim	No
Length (mm)	100
Net weight (kg)	0.74
IP internal	20

Download

[Mounting instructions](#)



Electrical

Emergency No

Notes

The closure terminals will also be electrified and must be ordered separately. Rod with a Ø140 connection rose: a supply rod for remote installation of the power supply through the connection rose. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED
Power supply

Electrical

60.8919

LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac



REQUIRED
Power supply

Electrical

60.9170

LED power supply source for remote installation, 48V/120W. 220/240 Vac



REQUIRED
Power supply

Electrical

60.9607

LED power supply source for remote installation, 110Vac-150W / 220Vac-200W



REQUIRED
Component

06.5135.14A

End Cap Dali/1-10V/FLOS Control@ by Casambi compatible



REQUIRED
Component

06.5135.40A

End Cap Dali/1-10V/FLOS Control@ by Casambi compatible



REQUIRED
Component

06.5142.14A

End Cap On board dimmer/FLOS Control@ by Casambi compatible



REQUIRED
Component

06.5142.40A

End Cap On board dimmer/FLOS Control@ by Casambi compatible