

FLOS

F018F31B012 Forest Green

In Vitro Rod 1

Designed by Philippe Starck, 2020



855lm - 3000K - CRI> 80 - Beam° 111

Rod installation. Light source is included. Power supply ON/OFF or dimmable 220-240V is integrated within the ceiling base. Length: 290 mm.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8054793319346
Mounting	Suspension
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Edge Lighting
Number of lamps	1
System power (W)	13
Lumen Output (lm)	855

Physical

Colour	Forest Green
Orientation	Fixed
Net weight (kg)	4.56
Package height (mm)	280
Package width (mm)	966
Package length (mm)	280
Package volume (m3)	0.08



Download

Mounting instructions [ZIP](#)

Photometric Files

LDT / IES [ZIP](#)

Technical Drawings

2D [ZIP](#)

3D [ZIP](#)




Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional

Schematic light drawing



Beam Angle: 111°

h(m)	E(lx)	D(m)
1	318	2.89
2	79	5.79
3	35	8.68
4	20	11.57
5	13	14.46

Luminous flux Luminaire
855 lm

Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	111
Beam angle C90-270 (°)	111

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 1-10V
Dimming interface	Dimmer Integrated

Accessories & Power Supply



OPTIONAL
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION
DEVICE)