

FLOS

F018F22B033 Anthracite

In Vitro Rod 2

Designed by Philippe Starck, 2020



799lm - 2700K - CRI> 80 - Beam° 111

Rod installation. Light source is included. Power supply ON/OFF or dimmable 220-240V is integrated within the ceiling base. Length: 390 mm.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8054793319049
Mounting	Suspension
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Edge Lighting
Number of lamps	1
System power (W)	13
Lumen Output (lm)	799

Physical

Colour	Anthracite
Orientation	Fixed
Net weight (kg)	4.56
Package height (mm)	280
Package width (mm)	966
Package length (mm)	280
Package volume (m3)	0.08



Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP



Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP




Ecodesign and Energy Labelling

   Replaceable (LED only) light source by a professional

  Replaceable control gear by a professional

Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	111
Beam angle C90-270 (°)	111

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 1-10V
Dimming interface	Dimmer Integrated

Accessories & Power Supply



OPTIONAL
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION
DEVICE)