

FLOS

08.8591.AAA Black

Junco 400 mm



Luminaire that offers many possibilities. Can be individually focused and their recessed height is adjustable.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
LED type	Power LED
Lamp category	LED
Power (W)	2.2
Source flux (lm)	216
Lumen Output (lm)	173

Physical

Colour	Black
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Recessed depth (mm)	360
Length (mm)	400
Net weight (kg)	0.19
IP internal	20
IP external	20



Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D



3D



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	15
Beam angle C90-270 (°)	15
UGR _L	<10

Electrical

Forward voltage (V)	3
Power supply	Remote excluded
Dimmable	No
Power supply type	Non Dimmable, Dimmable Push, Dimmable 1-10V
Emergency	No

Notes

Soft Plate to be order separately.

Accessories & Power Supply



OPTIONAL
Power supply
Electrical

60.8911
Non dimmable continuous current power supply of 15-20W, 110/240V - 50/60Hz, with power current selected through adjustable 350 mA-15W /500 mA / 550 / 700 / 850 mA / 900 mA - 20W switch



OPTIONAL
Power supply
Electrical

60.9188
Continuous current power supply of 13-20W, 110*/240V - 50/60Hz with current selected through adjustable 200 mA - 13W / 300 mA - 15W / 350 mA - 18W / 400 / 450 / 500 / 550 / 600 / 650 / 700 / 750 / 800 / 850 / 900 mA - 20W. switch. 0/1-10V or push.



OPTIONAL
Power supply
Electrical

60.9222
Continuous current power supply of 12-20W, 110/240V - 50/60Hz with power current selected through adjustable 250mA - 12W / 350mA - 17W / 400mA - 19W / 450 / 500/ 550 / 600 / 700mA - 20W regulable Dali 1 & Dali 2



OPTIONAL
Power supply
Electrical

60.9592
Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA - 15W / 400mA - 17W / 450mA - 19W / 500mA - 22W / 550mA - 24W / 600mA - 26W / 650mA - 28W / 700mA - 30W.



OPTIONAL
Power supply
Electrical

60.9692
30W, 220-240V - 50/60Hz
Constant current power supply, with dip-switch programmable power supply current.



OPTIONAL
Power supply
Electrical

60.9379
Mains Dimming, continuous current power supply 10W, 220/240V - 50/60Hz



OPTIONAL
Power supply
Electrical

60.9408
No dim continuous current power supply 13-20W, 220/240V - 50/60Hz



OPTIONAL
Power supply
Electrical

60.7785
Constant current power supply 42W, 220-240V CASAMBI dimmable.

