

FLOS

06.5116.40 White

Mechanical Rod Rose Ø 140 mm


Designed by Vincent Van Duysen, 2017



Mechanical rod rose ø140 mm. Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Ceiling surface |
| Environments | Indoor dry location |
| Light sources included | no |
| Number of lamps | 1 |

Physical

| | |
|-----------------|-------|
| Colour | White |
| Trim | No |
| Length (mm) | 300 |
| Net weight (kg) | 0.84 |
| IP internal | 20 |

Download

[Mounting instructions](#)



Electrical

Emergency No

Notes

The closure terminals will also be electrified and must be ordered separately.
Mechanic rod with a Ø50 connection rose: to fasten profiles. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED
Component

06.5135.14A

End Cap Dali/1-10V/FLOS
Control® by Casambi compatible



REQUIRED
Component

06.5135.40A

End Cap Dali/1-10V/FLOS
Control® by Casambi compatible



REQUIRED
Component

06.5142.14A

End Cap On board dimmer/FLOS
Control® by Casambi compatible



REQUIRED
Component

06.5142.40A

End Cap On board dimmer/FLOS
Control® by Casambi compatible