

Mechanical Rod Rose Ø 50 mm


Designed by Vincent Van Duysen, 2017



Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light sources included | no                  |
| Number of lamps        | 1                   |

### Physical

|                 |       |
|-----------------|-------|
| Colour          | Black |
| Trim            | No    |
| Length (mm)     | 100   |
| Net weight (kg) | 0.45  |
| IP internal     | 20    |
| IP external     | 20    |

### Download

Mounting instructions



### Electrical

Emergency No

### Notes

The closure terminals will also be electrified and must be ordered separately.  
Mechanic rod with a Ø50 connection rose: to fasten profiles. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED  
Component

06.5135.14A  
End Cap Dali/1-10V/FLOS  
Control® by Casambi compatible

REQUIRED  
Component

06.5135.40A  
End Cap Dali/1-10V/FLOS  
Control® by Casambi compatible

REQUIRED  
Component

06.5142.14A  
End Cap On board dimmer/FLOS  
Control® by Casambi compatible

REQUIRED  
Component

06.5142.40A  
End Cap On board dimmer/FLOS  
Control® by Casambi compatible