

## My Spot Ø35 Long Recessed NEW

Designed by FLOS Architectural, 2024



LED - LED array - 7.4W - 599lm - 3000K - CRI> 90 - Beam° 20

LED lighting module for recessed applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

|                   |           |
|-------------------|-----------|
| Mounting          | Recessed  |
| LED type          | LED array |
| Lamp category     | LED       |
| Number of lamps   | 1         |
| Power (W)         | 7.4       |
| System power (W)  | 11        |
| Source flux (lm)  | 711       |
| Lumen Output (lm) | 599       |

### Physical

|                          |                |
|--------------------------|----------------|
| Colour                   | Brushed Bronze |
| Rotation (°)             | 360            |
| Longitudinal tilting (°) | 90             |
| Recessed depth (mm)      | 50             |
| Net weight (kg)          | 0.6            |
| IP internal              | 20             |
| IP external              | 20             |



### Download

Mounting instructions [↓ PDF](#)


### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)




### Ecodesign and Energy Labelling

 Non-replaceable light source

 Replaceable control gear by a professional

Schematic light drawing



Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Direct                |
| Light distribution       | Symmetric             |
| CCT (K)                  | 3000                  |
| CRI>                     | 90                    |
| McAdam steps (SDCM)      | 2                     |
| Rf fidelity index        | 90                    |
| Rg gamut index           | 100                   |
| LED Life / Failure Ratio | L90B50>50.000h_Tc85°C |
| Beam angle C0-180 (°)    | 20                    |
| Beam angle C90-270 (°)   | 20                    |
| Extreme cut off          | No                    |
| UGR <sub>L</sub>         | <10                   |

Electrical

|                     |                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------|
| Insulation class    | III                                                                                                              |
| Forward voltage (V) | 18                                                                                                               |
| LED current (mA)    | 400                                                                                                              |
| Power supply        | Remote                                                                                                           |
| Dimmable            | Yes                                                                                                              |
| Power supply type   | Non Dimmable,<br>Dimmable DALI 2,<br>Dimmable Casambi,<br>Dimmable Push,<br>Dimmable 1-10V,<br>Mains Cut Dimming |
| Batteries inside    | No                                                                                                               |

Accessories & Power Supply



REQUIRED  
Power supply

Electrical

60.9208

Continuous current power supply of 13-20W - Dim 1-10V&Push - 110/240V - 50/60Hz with power current selected through adjustable



REQUIRED  
Power supply

Electrical

60.7773

Constant current power supply 28W, 220-240V - 50/60Hz with programmable output current via DIP switch. 100mA - 5.4W / 150mA - 7.9W / 200mA - 10.4W / 250mA - 13W / 300mA - 15.5W / 350mA - 18W / 400mA - 20.4W / 450mA - 23W / 500mA - 25.8W / 550mA - 28.4W...



REQUIRED  
Power supply

Electrical

60.7774

Constant current power supply 20W, 220-240V - 50/60Hz with programmable output current via DIP switch. 100mA - 5.8W / 150mA - 8.3W / 200mA - 10.8W / 250mA - 13.2W / 300mA - 15.6W / 350mA - 18.1W / 400mA - 20.6W / 450mA - 23W / 500mA - 22.9W / 550mA - 2...



REQUIRED  
Power supply

Electrical

60.7661

Constant current power supply 15W, 220-240V - 50/60Hz with programmable output current via DIP switch. 400mA - 11.6W / 450mA - 13W / 500mA - 14.5W / 550mA - 15.9W. Phase-cut dimmable (Triac).



REQUIRED  
Power supply

Electrical

60.7785

Constant current power supply 42W, 220-240V CASAMBI dimmable.