

FLOS

09.8220.DY Matte White

Oblique Floor ONLINE EXCLUSIVE


Designed by Vincent Van Duysen

LED - Top LED - 8W - 479lm - 2700K - CRI> 90 - Beam° 34

Floor lamp that, thanks to its innovative patented lens, offers asymmetrical light distribution and excellent visual comfort. Its shape, height and dimensions are consistent with the functionality of the product, which provides excellent reading or companion lighting while keeping the light source invisible to the user. Driver input: 24 V

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Floor |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Top LED |
| Lamp category | LED |
| Number of lamps | 1 |
| Power (W) | 8 |
| System power (W) | 10 |
| System flux (lm) | 479 |

Physical

| | |
|---------------------|-------------|
| Colour | Matte White |
| Length (mm) | 200 |
| Cord length (mm) | 2500 |
| Net weight (kg) | 3.32 |
| Package height (mm) | 120 |
| Package width (mm) | 30 |
| Package length (mm) | 30 |
| IP internal | 20 |

Download

Mounting instructions [PDF](#)



Photometric Files

LDT / IES [ZIP](#)



Technical Drawings

2D [ZIP](#)




3D [ZIP](#)




BIM [ZIP](#)



Schematic light drawing



Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by an end-user

Photometric

| | |
|--------------------------|----------------------------|
| Lighting type | Direct |
| Light distribution | Asymmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| McAdam steps (SDCM) | 3 |
| LED Life / Failure Ratio | L90B10 > 50.000h (Tc=85°C) |
| Beam angle C0-180 (°) | 34 |
| Beam angle C90-270 (°) | 46 |

Electrical

| | |
|---------------------|-----------------|
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 110-240 |
| Forward voltage (V) | 24 |
| Power supply | Remote included |
| Dimmable | Yes |
| Power supply type | Dimmer on board |
| Dimming range (%) | 1-100 |
| Precabled | Yes |
| Plug type | Twist and Lock |