

FLOS

09.8222.DV Glossy Sage

Oblique Floor ONLINE EXCLUSIVE


Designed by Vincent Van Duysen

LED - Top LED - 525lm - 4000K - CRI> 90 - Beam° 34

Floor lamp that, thanks to its innovative patented lens, offers asymmetrical light distribution and excellent visual comfort. Its shape, height and dimensions are consistent with the functionality of the product, which provides excellent reading or companion lighting while keeping the light source invisible to the user. Driver input: 24 V

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Floor
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
System power (W)	18
System flux (lm)	525

Physical

Colour	Glossy Sage
Length (mm)	200
Cord length (mm)	2500
Net weight (kg)	3.32
Package height (mm)	120
Package width (mm)	30
Package length (mm)	30
IP internal	20

Download

Mounting instructions [Download PDF](#)

Photometric Files

LDT / IES [Download ZIP](#)

Technical Drawings


2D [Download ZIP](#)

3D [Download ZIP](#)


[Bim](#) [Download ZIP](#)




Schematic light drawing



Ecodesign and Energy Labelling



Non-replaceable light source



Replaceable control gear by an end-user

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L90B10 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	34
Beam angle C90-270 (°)	46

Electrical

Frequency (Hz)	50/60
Main voltage (Vac)	110-240
Forward voltage (V)	24
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmer on board
Dimming range (%)	1-100
Precabled	Yes
Plug type	Twist and Lock