

09.9084.BWA White

The Fast Track Spot 150 Casambi integrated

NEW


Designed by FLOS Architectural, 2020



Spotlight to be installed in the The Fast Track system profile with a LED light source and glass optics: high performance spot, medium and flood lights.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	25.5
Source flux (lm)	2378
Lumen Output (lm)	1792

Physical

Colour	White
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	57
Length (mm)	240
Net weight (kg)	0.83
IP internal	20

Download

Mounting instructions [ZIP](#)

Photometric Files

LDT / IES [ZIP](#)

Technical Drawings


2D [ZIP](#)

3D [ZIP](#)

[Bim](#) [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	27
Beam angle C90-270 (°)	27
Extreme cut off	No
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	550
Power supply	Remote excluded
Power supply type	Dimmable Casambi

Notes

The boxes of the luminaries are manufactured only in black. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

Accessories & Power Supply



OPTIONAL
Accessory
Optical

08.0526.00


Snoot shielding cone



OPTIONAL
Accessory
Optical

08.8428.00

Honeycomb



OPTIONAL
Accessory
Optical

08.8429.00

Screening crosspiece



OPTIONAL
Accessory
Optical

08.8431.00


Elliptical lens



OPTIONAL
Accessory
Optical

08.8432.00


Flood lens



OPTIONAL
Accessory
Optical

08.0526.40

Snoot shielding cone



OPTIONAL
Accessory
Optical

08.0526.BW

Snoot shielding cone