

FLOS

06.1640.14 Black

The Running Magnet Recessed Feed Unit Profile


Designed by FLOS Architectural, 2015



'Electromechanical profile for recessed installation in plasterboard ceilings and walls. Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------------------|
| Mounting | Wall recessed, Ceiling recessed |
| Environments | Indoor dry location |
| Light sources included | no |

Physical

| | |
|---------------------|-------|
| Colour | Black |
| Trim | No |
| Recessed depth (mm) | 86 |
| Length (mm) | 2000 |
| Net weight (kg) | 6.60 |
| IP internal | 20 |
| IP external | 20 |

Download

[Mounting instructions](#)

[ZIP](#)



Electrical

| | |
|---------------------|---|
| Forward voltage (V) | 24 |
| Power supply | Remote excluded |
| Power supply type | Non Dimmable, Dimmable DALI 2, Dimmable Casambi |

Notes

The Recessed version can only be installed on 12.5 mm thick plasterboard surfaces. Covers included with the power feed profiles. 90° corners available in the same plane (symmetrical element for left and right corners), symmetrical 90° inner and outer corners in different planes. For connection to the driver. Permanent or adjustable fastening kits available (optional). The fastening kits for the roof permit installing without using aluminium fastening profiles. Recommended for installations where the Running Magnet 2.0 cannot be installed before the suspended plasterboard ceiling (use 2 units).

Accessories & Power Supply



REQUIRED
Power supply

Electrical

60.9352

LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.



REQUIRED
Power supply

Electrical

60.9089

Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W



REQUIRED
Power supply

Electrical

60.9407

Electronic transformer with constant voltage (24V) for LED. 100/240V. 120W



REQUIRED
Installation

08.8865.14A

Endcap. 2 unit kit



OPTIONAL

Installation

08.8866.14

Fixed ceiling kit. 2 unit kit



OPTIONAL

Installation

08.8867.14

Adjustable ceiling kit. 2 unit kit



OPTIONAL

Electrical

06.1987.14

Multifunction Smart Device for Running Magnet & Fast Track



OPTIONAL

Electrical

06.1987.40

Multifunction Smart Device for Running Magnet & Fast Track