

The Tracking Magnet Recessed Profile Casambi / On Board Dimmer compatible

Designed by FLOS Architectural, 2018



Electromechanical profile for recessed installation in plasterboard ceilings and walls, available in lengths from 1m to 3m.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Wall recessed, Ceiling recessed
Environments	Indoor dry location
Light sources included	no

Physical

Colour	Black
Trim	No
Field cuttable	Yes
Recessed depth (mm)	45
Length (mm)	1500
Net weight (kg)	1.87
IP internal	20
IP external	20



Download

Mounting instructions

↓ PDF

Electrical

Forward voltage (V)	48
Power supply	Remote
Dimmable	Yes
Power supply type	Dimmer on board, Dimmable Casambi
Emergency	No

Notes

Version compatible with "On board dimmer" luminaries and version compatible with system controlled luminaries (DALI, 1-10V, FLOS SMART CONTROL) available. Corners, connectors and accessories common for the two profile versions. Feed connector, intermediated connector and end-caps to be ordered separately. Mechanical 90° corners available in the same plane (symmetrical element for left and right corners), symmetrical 90° inner and outer corners in different planes. Intermediate connectors to be ordered separately if electrical continuity on corners is required. Corners do not admit installation of spots. Fixed or adjustable fastening kits available (optional). The fastening kits for the roof permit installing without using aluminium fastening profiles. Recommended for installations where the Tracking Magnet can be installed before the suspended plasterboard ceiling.

Accessories & Power Supply



REQUIRED
Power supply
Electrical

60.8919
LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac



REQUIRED
Power supply
Electrical

60.9170
LED power supply source for remote installation, 48V/120W. 220/240 Vac



REQUIRED
Power supply
Electrical

60.9607
LED power supply source for remote installation, 110Vac-150W / 220Vac-200W



REQUIRED
Accessory
06.5008.14
The Tracking Magnet Recessed Profile End Caps



REQUIRED
Accessory
Electrical

08.0611.14
The Tracking Magnet Profile Feed Connector



REQUIRED
Accessory
Electrical

08.0612.14
The Tracking Magnet Profile Intermediate Connector Straight



REQUIRED
Installation

08.8866.14
Fixed ceiling kit. 2 unit kit



REQUIRED
Installation

08.8867.14
Adjustable ceiling kit. 2 unit kit



REQUIRED

Electrical

06.1988.14

Multifunction Smart Device for
Tracking Magnet & Infra-Structure