

# FLOS

60.3820.11ADA Matte White


## Three Phase Track Recessed Dali 2000 mm

Designed by FLOS Architectural, 2014

Length: 2000 - Wall recessed, Ceiling recessed



GLOBAL TRACK offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBAL TRACK lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height. Other advantages of the three-circuit system are its high loading capacity and the possibility of forming independent fixture groups in all three circuits. This permits illumination of the most demanding environments.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Wall recessed, Ceiling recessed
Environments	Indoor dry location

### Physical

Colour	Matte White
Trim	No
Length (mm)	2000
Net weight (kg)	0.80
IP internal	20
IP external	20

### Download

[Mounting instructions](#)

[↓ PDF](#)



## Electrical

Insulation class I

---

Emergency No

## Accessories & Power Supply



OPTIONAL  
Accessory

Installation

60.3016.11

Blind end



OPTIONAL  
Accessory

60.3016.12

Blind end



OPTIONAL  
Accessory

60.3016.14

Blind end



OPTIONAL  
Accessory

Installation

60.3022.11

Recessed box for fix-point



OPTIONAL  
Accessory

Installation

60.3022.14

Recessed box for fix-point



OPTIONAL  
Accessory

Installation

60.3023.11

Fix-point



OPTIONAL  
Accessory

Installation

60.3023.14

Fix-point



OPTIONAL  
Accessory

Electrical

60.3028.11ADA

Connector 90° Outside Dali



OPTIONAL  
Accessory

60.3028.14ADA

Connector 90° Outside Dali



OPTIONAL  
Accessory

Electrical

60.3028.29ADA

Connector 90° Outside Dali



OPTIONAL  
Accessory

Electrical

60.3029.11ADA

Connector 90° Inside Dali



OPTIONAL  
Accessory

Electrical

60.3029.14ADA

Connector 90° Inside Dali



OPTIONAL  
Accessory

Electrical

60.3029.29ADA

Connector 90° Inside Dali



OPTIONAL  
Accessory

Electrical

60.3036.11ADA

Cross Coupling Dali



OPTIONAL  
Accessory

Electrical

60.3036.14ADA

Cross Coupling Dali



OPTIONAL  
Accessory

Electrical

60.3036.29ADA

Cross Coupling Dali



OPTIONAL  
Accessory

Electrical

60.3043.11ADA

Mean connector Dali



OPTIONAL  
Accessory

Electrical

60.3043.14ADA

Mean connector Dali



OPTIONAL  
Accessory

Electrical

60.3043.29ADA

Mean connector Dali



OPTIONAL  
Accessory

60.3044.11ADA

Straight Connector Dali



OPTIONAL  
Accessory

Electrical

60.3044.12ADA

Straight Connector Dali



OPTIONAL  
Accessory

Electrical

60.3044.14ADA

Straight Connector Dali



OPTIONAL  
Accessory

Installation

60.3047.11ADA

Connector T - Inside Right Dali



OPTIONAL  
Accessory

Installation

60.3047.14ADA

Connector T - Inside Right Dali



OPTIONAL  
Accessory

Installation

60.3047.29ADA

Connector T - Inside Right Dali



OPTIONAL  
Accessory

Installation

60.3048.11ADA

Connector T - Inside Left Dali



OPTIONAL  
Accessory

Installation

60.3048.14ADA

Connector T - Inside Left Dali



OPTIONAL  
Accessory

Installation

60.3048.29ADA

Connector T - Inside Left Dali



OPTIONAL  
Accessory

Installation

60.3053.11

Cover for power supply  
connectors recessed track



OPTIONAL  
Accessory

Installation

60.3053.14

Cover for power supply  
connectors recessed track



OPTIONAL  
Accessory

Mounting

60.3054

Lead bending key



OPTIONAL  
Accessory

Installation

60.3146.11

Cover for connectors DALI



OPTIONAL  
Accessory

Installation

60.3146.14

Cover for connectors DALI



OPTIONAL  
Accessory

Installation

60.3023.29

Fix-point