


# FLOS


60.3102.11ADA Matte White

## Three Phase Track Surface/Pendant Dali 2000 mm

Length: 2000 - Suspension, Ceiling surface



GLOBAL PRO offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBAL PRO lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height. Other advantages of the three-circuit system are its high loading capacity and the possibility of forming independent fixture groups in all three circuits. This permits illumination of the most demanding environments.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Suspension, Ceiling surface
Environments	Indoor dry location

### Physical

Colour	Matte White
Trim	No
Length (mm)	2000
Net weight (kg)	0.80
IP internal	20
IP external	20

### Download

[Mounting instructions](#)

[↓ PDF](#)



## Electrical

Insulation class I

---

Emergency No

## Accessories & Power Supply



OPTIONAL  
Accessory

60.3008.11

Attachment on track for steel cable suspension with M6 thread end



OPTIONAL  
Accessory

60.3008.14

Attachment on track for steel cable suspension with M6 thread end



OPTIONAL  
Accessory

Installation

60.3014.14

1 m suspension rod with ceiling rose kit, M6 thread



OPTIONAL  
Accessory

Installation

60.3016.11

Blind end



OPTIONAL  
Accessory

60.3016.12

Blind end



OPTIONAL  
Accessory

60.3016.14

Blind end



OPTIONAL  
Accessory

60.3018.11

Attachment on track for rod suspension M6 thread



OPTIONAL  
Accessory

Electrical

60.3018.14

Attachment on track for rod suspension M6 thread



OPTIONAL  
Accessory

Installation

60.3025.11

Bracket



OPTIONAL  
Accessory

Installation

60.3025.14

Bracket



OPTIONAL  
Accessory

Installation

60.3025.29

Bracket



OPTIONAL  
Accessory

Electrical

60.3028.11ADA

Connector 90° Outside Dali



OPTIONAL  
Accessory

60.3028.14ADA

Connector 90° Outside Dali



OPTIONAL  
Accessory

Electrical

60.3028.29ADA

Connector 90° Outside Dali



OPTIONAL  
Accessory

Electrical

60.3029.11ADA

Connector 90° Inside Dali



OPTIONAL  
Accessory

Electrical

60.3029.14ADA

Connector 90° Inside Dali



OPTIONAL  
Accessory

Electrical

60.3029.29ADA

Connector 90° Inside Dali



OPTIONAL  
Accessory

Electrical

60.3036.11ADA

Cross Coupling Dali




OPTIONAL  
Accessory

Electrical

60.3036.14ADA

Cross Coupling Dali



OPTIONAL  
Accessory

Electrical

60.3036.29ADA

Cross Coupling Dali



OPTIONAL  
Accessory

Electrical

60.3043.11ADA

Mean connector Dali



OPTIONAL  
Accessory

Electrical

60.3043.14ADA

Mean connector Dali



OPTIONAL  
Accessory

Electrical

60.3043.29ADA

Mean connector Dali



OPTIONAL  
Accessory

60.3044.11ADA

Straight Connector Dali



OPTIONAL  
Accessory

Electrical

60.3044.12ADA

Straight Connector Dali



OPTIONAL  
Accessory

Electrical

60.3044.14ADA

Straight Connector Dali



OPTIONAL  
Accessory

Installation

60.3047.11ADA

Connector T - Inside Right Dali



OPTIONAL  
Accessory

Installation

60.3047.14ADA

Connector T - Inside Right Dali



OPTIONAL  
Accessory

Installation

60.3047.29ADA

Connector T - Inside Right Dali



OPTIONAL  
Accessory

Installation

60.3048.11ADA

Connector T - Inside Left Dali



OPTIONAL  
Accessory

Installation

60.3048.14ADA

Connector T - Inside Left Dali



OPTIONAL  
Accessory

Installation

60.3048.29ADA

Connector T - Inside Left Dali



OPTIONAL  
Accessory

Mounting

60.3054

Lead bending key



OPTIONAL  
Accessory

Installation

60.3057.11

Attachment on track for wire  
suspension



OPTIONAL  
Accessory

Installation

60.3057.29

Attachment on track for wire  
suspension



OPTIONAL  
Accessory

Installation

60.3092.11

Power supply rose cover



OPTIONAL  
Accessory

Installation

60.3094.11

Ceiling fitting with rose



OPTIONAL  
Accessory

Installation

60.3094.14

Ceiling fitting with rose



OPTIONAL  
Accessory

Installation

60.3095.29

Lead-weighted wire 1500 mm



OPTIONAL  
Accessory

Installation

60.3097.11

1 m suspension rod with ceiling  
rose with m6 thread



OPTIONAL  
Accessory

Installation

60.3097.14

1 m suspension rod extension  
set with m6 thread



OPTIONAL  
Accessory

Installation

60.3090.11A

Track cover strip L 2000 mm



OPTIONAL  
Accessory

Installation

60.3090.14A

Track cover strip L 2000 mm



OPTIONAL  
Accessory

Electrical

60.3037.14ADA

DALI Flexible connector



OPTIONAL  
Accessory

Electrical

60.3037.11ADA

DALI Flexible connector



OPTIONAL  
Accessory

Electrical

60.3038.11ADA

Live end right Dali



OPTIONAL  
Accessory

Electrical

60.3038.14ADA

Live end right Dali



OPTIONAL  
Accessory

Electrical

60.3038.12ADA

Live end right Dali



OPTIONAL  
Accessory

Electrical

60.3039.14ADA

Live end left Dali



OPTIONAL  
Accessory

Electrical

60.3039.12ADA

Live end left Dali



OPTIONAL  
Accessory

Electrical

60.3039.11ADA

Live end left Dali



OPTIONAL  
Accessory

Installation

60.3083.29

Complete wall support 70 mm



OPTIONAL  
Accessory

60.3093.29

Bracket for fixing track to wall or ceiling



OPTIONAL  
Accessory

Installation

60.3014.11

Suspension rod with 1m rose.  
M6 thread



OPTIONAL  
Accessory

Installation

60.3096.29

Lead-weighted wire 3000 mm