

# FLOS

09.7215.14C Black

## UT Pro 150 On Board Dimmer

Designed by FLOS Architectural, 2017



Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
System power (W)	21

### Physical

Colour	Black
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	57
Net weight (kg)	0.56
IP internal	20



### Download

Mounting instructions [PDF](#)



### Photometric Files

LDT / IES



### Technical Drawings


2D



3D



## Schematic light drawing



Beam Angle: 36°		
h(m)	E(k)	D(m)
1	5199	0.64
2	1300	1.28
3	578	1.92
4	325	2.56
5	208	3.20

## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	90
Extreme cut off	No


## Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	120-277
LED current (mA)	500
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmer on board
Dimming range (%)	10-100
Dimming interface	Dimmer Integrated

## Ecodesign and Energy

### Labelling

This product contains a light source of energy efficiency class **G**



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

## Notes

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

## Accessories & Power Supply



### OPTIONAL Accessory

Optical

08.0526.00

Snoot shielding cone

### OPTIONAL Accessory

Optical

08.8428.00

Honeycomb

### OPTIONAL Accessory

Optical

08.8429.00

Screening crosspiece

### OPTIONAL Accessory

Optical

08.8431.00

Elliptical lens



### OPTIONAL Accessory

Optical

08.8432.00

Flood lens

### OPTIONAL Accessory

Optical

08.0526.40

Snoot shielding cone

### OPTIONAL Accessory

Optical

08.0526.BW

Snoot shielding cone