

FLOS

09.7210.40C78 White/White

UT Pro 150 On Board Dimmer All White


Designed by FLOS Architectural, 2017



Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
System power (W)	20.1
Source flux (lm)	2524
Lumen Output (lm)	2266
Efficacy (lm/W)	112.74

Physical

Colour	White/White
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	57
Net weight (kg)	0.56
IP internal	20

Download

Mounting instructions [PDF](#)



Photometric Files

LDT / IES



Technical Drawings


2D



3D



Schematic light drawing



Beam Angle: 21°		
<u>h</u> (m)	<u>E</u> (k)	<u>D</u> (m)
1	14010	0.37
2	3503	0.74
3	1557	1.11
4	876	1.48
5	560	1.85

Luminous flux luminaire
2266 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	80
LED Life / Failure Ratio	L80B50 >50.000h (T _c =85°C)
Beam angle C0-180 (°)	21
Beam angle C90-270 (°)	21
Extreme cut off	No


Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	120-277
LED current (mA)	470
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmer on board
Dimming range (%)	10-100
Dimming interface	Dimmer Integrated


Ecodesign and Energy

Labelling

This product contains a light source of energy efficiency class **G**



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional

Notes

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

Accessories & Power Supply



OPTIONAL Accessory

Optical

08.0526.00

Snoot shielding cone

OPTIONAL Accessory

Optical

08.8428.00

Honeycomb

OPTIONAL Accessory

Optical

08.8429.00

Screening crosspiece

OPTIONAL Accessory

Optical

08.8431.00

Elliptical lens



OPTIONAL Accessory

Optical

08.8432.00

Flood lens

OPTIONAL Accessory

Optical

08.0526.40

Snoot shielding cone

OPTIONAL Accessory

Optical

08.0526.BW

Snoot shielding cone