

FLOS

09.7213.40C78 White/White

UT Pro 150 On Board Dimmer All White

Designed by FLOS Architectural, 2017



Spotlight to be installed in Tracking Power profile with LED light source. 120-277V power supply integrated. High performance reflector included. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white. Only the anti-glare ring is black.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

| | |
|------------------------|---------------------|
| Mounting | Track |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | LED array |
| Lamp category | LED |
| Number of lamps | 1 |
| System power (W) | 21 |
| Source flux (lm) | 2360 |
| Lumen Output (lm) | 1779 |

Physical

| | |
|--------------------------|-------------|
| Colour | White/White |
| Trim | No |
| Orientation | Adjustable |
| Rotation (°) | 360 |
| Longitudinal tilting (°) | 90 |
| Spot diameter (mm) | 57 |
| Net weight (kg) | 0.56 |
| IP internal | 20 |



Download

Mounting instructions [PDF](#)



Photometric Files

LDT / IES [ZIP](#)



Technical Drawings


2D [ZIP](#)



3D [ZIP](#)



Schematic light drawing



Photometric

| | |
|------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 4000 |
| CRI> | 90 |
| Beam angle C0-180 (°) | 27 |
| Beam angle C90-270 (°) | 27 |
| Extreme cut off | No |


Electrical

| | |
|--------------------|-------------------|
| Insulation class | II |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 120-277 |
| LED current (mA) | 500 |
| Power supply | Integrated |
| Dimmable | Yes |
| Power supply type | Dimmer on board |
| Dimming range (%) | 10-100 |
| Dimming interface | Dimmer Integrated |


Ecodesign and Energy

Labelling

This product contains a light source of energy efficiency class **G**



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional

Notes

Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.

Accessories & Power Supply



OPTIONAL Accessory

Optical

08.0526.00

Snoot shielding cone

OPTIONAL Accessory

Optical

08.8428.00

Honeycomb

OPTIONAL Accessory

Optical

08.8429.00

Screening crosspiece

OPTIONAL Accessory

Optical

08.8431.00

Elliptical lens



OPTIONAL Accessory

Optical

08.8432.00

Flood lens

OPTIONAL Accessory

Optical

08.0526.40

Snoot shielding cone

OPTIONAL Accessory

Optical

08.0526.BW

Snoot shielding cone