

FLOS

09.7504.40.DA White


UT Pro Wall-Washer Dali Version GA-600

Designed by FLOS Architectural, 2017



LED - Top LED - 25.2W - 1554lm - 3000K - Beam° 36

Wall-Washer lighting module to be installed in standard 3-phase track with LED light source. 220-240V power supply integrated. DALI version requires dimmable tracks (please refer to the "Tracks" chapter). .40 versions come with the track adapter, the arm and the rear of the head in black.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	25.2
System power (W)	25.5
Source flux (lm)	3176.6
Lumen Output (lm)	1554

Physical

Colour	White
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	15
Length (mm)	420
Net weight (kg)	1.05
IP internal	20
IP external	20

Download

Mounting instructions [PDF](#)



Item information [JPG](#)



Photometric Files

LDT / IES [ZIP](#)



Technical Drawings

2D [ZIP](#)




3D [ZIP](#)



Bim [ZIP](#)




Schematic light drawing




Beam Angle: 36°		
$h(m)$	$E(k)$	$D(m)$
1	1083	0.76
2	271	1.52
3	120	2.28
4	68	3.04
5	43	3.80

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
Beam angle C0-180 (°)	36
Beam angle C90-270 (°)	75

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Alternating current voltage (Vac)	230
LED current (mA)	700
Power supply	Integrated
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)

Emergency No