

FLOS

09.7505.40.78 White/White


UT Pro Wall-Washer GA-69 All White

Designed by FLOS Architectural, 2017



LED - Top LED - 25.2W - 1700lm - 4000K - CRI> 90 - Beam° 36

Wall-Washer lighting module to be installed in standard 3-phase track with LED light source. 220-240V power supply integrated. In the "All white" versions, the track adapter, the arm, the rear of the head and the head are white.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	25.2
System power (W)	25.5
Source flux (lm)	3154
Lumen Output (lm)	1700

Physical

Colour	White/White
Trim	No
Orientation	Adjustable
Rotation (°)	360
Length (mm)	420
Net weight (kg)	1.05
IP internal	20
IP external	20

Download

Mounting instructions	PDF
Item information	JPG

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP
BIM	ZIP




Schematic light drawing



Beam Angle: 36°		
h(m)	E(k)	D(m)
1	1184	0.76
2	296	1.52
3	132	2.28
4	74	3.04
5	47	3.80

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	90
Beam angle C0-180 (°)	36
Beam angle C90-270 (°)	75
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Alternating current voltage (Vac)	230
LED current (mA)	700
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No