

X Connector Feed Dimmable

NEW

Designed by FLOS Architectural, 2023



Ceiling surface, Wall surface

Cross-shaped connector. Can be powered via connections on the back. Rear feeding cable entry.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling surface, Wall surface
Environments	Indoor dry location
Light sources included	No

Physical

Colour	Black
Net weight (kg)	0.03
IP internal	20



Download

Mounting instructions



Electrical


Insulation class	III
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)

Accessories & Power Supply



REQUIRED
Power supply
Electrical

60.9352
LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.




REQUIRED
Power supply
Electrical

60.9705
Remote Power Supply Non Dimmable 24V. 60W. 220/240V



REQUIRED
Power supply
Electrical

60.9777A
Remote Power Supply Non Dimmable 24V. 120W. 220/240V



OPTIONAL
Power supply
Electrical

08.0613.14A
Dimmable control box 1-10V, 24/48V. For remote installation.